CHASEERWIN

LEATHER SPECIFICATION SHEET

Fabric: Goodwood

Composition: Bovine leather of European origin

Average Hide Size: 4.8 - 5.0 sqm

Thickness: 0.8-1.0mm

Finish:

Lightly buffed natural grain.

Aniline dyed, finished with waxes for a distressed appearance.

Natural unprotected surface.

Hides have an uneven, slick feel, with a semi-gloss appearance.

Chrome tanning.

Flammability:

BS: 5852: 1979: Passes BS EN 1021-1-2:2006: Passes

Colour Fastness to Rubbing:

UNI EN ISO 11640: Dry -50 C > 3 / Wet -20 c > 3 / Sweat -20 c > 2

ISO 105 A03

Perspiration Alkaline Solution (ISO 11641 pH 8)

Colour Fastness to Artificial Light:

UNI EN ISO 05 BO2: Blue Scale > 2 / 3

Flexing Endurance:

ISO 5402: Cycles > 50,000

pH Value:

ISO 4045: pH > 3.5 (<0.7 variance)

Tear Strength:

ISO 3377-1: N > 20

Maintenance and cleaning:

For normal cleaning we suggest dusting with a soft dry cloth.

Avoid abrasive or aggressive products such as solvents and stain removers or shoe products.

We do not recommend using steam for cleaning.

Avoid placing the leather in direct sun light.

Avoid contact between light and dark colours between different materials.

Keep away from direct heat.

1 hide minimum when ordering.

^{*}Leather is not guaranteed against wear, fading or dye lot variation.