

CHASE ERWIN

LEATHER SPECIFICATION SHEET

Fabric: Sebring

Composition: Bovine leather of European origin

Average Hide Size: 4.8 – 5.0 sqm

Thickness: 1.2-1.4mm

Finish:

Lightly buffed natural grain.

Through dyed, finished with resin and pigments.

Finished with a pigmented and protective coat, with a soft, waxy feel and semi-matt appearance.

Flammability:

BS: 5852: 1979: Passes

BS EN 1021-1-2: 2006: Passes

IMO RES A 652 (16): Passes

Colour Fastness to Rubbing:

UNI EN ISO 11640: Dry – 500 C > 4 / Wet – 250 c > 3/4 / Sweat – 80 c > 3/4

ISO 105 A03

Perspiration Alkaline Solution (ISO 11641 pH 8)

Colour Fastness to Artificial Light:

UNI EN ISO 05 B02: Blue Scale > 5

Finish Adhesion:

ISO 11644: N/Cm > 2.5

Flexing Endurance:

ISO 5402: Cycles > 50,000

pH Value:

ISO 4045: pH > 3.5 (>0.7 variance)

Tear Strength:

ISO 3377-1: N > 20

Maintenance and cleaning:

For normal cleaning we suggest dusting with a soft dry cloth.

Avoid abrasive or aggressive products such as solvents and stain removers or shoe products.

We do not recommend using steam for cleaning.

Avoid placing the leather in direct sun light.

Avoid contact between light and dark colours between different materials.

Keep away from direct heat.

*Leather is not guaranteed against wear, fading or dye lot variation.

1 hide minimum when ordering.