CHASEERWIN

LEATHER SPECIFICATION SHEET

Fabric: Silverstone

Composition: Bovine leather of European origin

Average Hide Size: 4.8 - 5.0 sqm

Thickness: 0.9-1.1mm

Finish:

Full grain.

Aniline dyed, finished with oils, natural waxes, and resins.

Hides have a firm, waxy feel, and shiny appearance, with a light two-tone effect.

Chrome tanning.

Flammability:

BS: 5852: 1979: Passes

BS EN 1021-1-2: 2006: Passes

Colour Fastness to Rubbing:

UNI EN ISO 11640: Dry -50 C > 4 / Wet -20 c > 4 / Sweat -20 c > 4

ISO 105 A03

Perspiration Alkaline Solution (ISO 11641 pH 8)

Colour Fastness to Artificial Light:

UNI EN ISO 05 BO2: Blue Scale > 2

Flexing Endurance:

ISO 5402: Cycles > 50,000

pH Value:

ISO 4045: pH > 3.5 (>0.7 variance)

Tear Strength:

ISO 3377-1: N > 20

Maintenance and cleaning:

For normal cleaning we suggest dusting with a soft dry cloth.

Avoid abrasive or aggressive products such as solvents and stain removers or shoe products.

We do not recommend using steam for cleaning.

Avoid placing the leather in direct sun light.

Avoid contact between light and dark colours between different materials.

Keep away from direct heat.

1 hide minimum when ordering.

^{*}Leather is not guaranteed against wear, fading or dye lot variation.